

## ‘Purity Monitor’

Features:

Measures electron drift lifetime (function of E field?) (few %)

Self-calibrating:

Can determine drift-velocity (at E-field of PrM), and so  
sensitive to Temperature (fraction of a K).

LArTPC Document Database

http://lartpc-docdb.fnal.gov/ Google

HHT LB rap.. D&S me ATWK Beam Logs Trit LAr fone IMP1 Req? PO? LIST lbin LFC Cwth Lbry stgrp Gar VMS PSC >>

# LArTPC Document Database

**Public**  
**Private** - *password required*


---

[Security, Privacy, Legal](#)  
[Fermilab Policy on Computing](#)

Fermi National Accelerator Laboratory

For assistance contact [HelpDesk](#)  
Last Modified by MT on 6 February 2006  
[DocDB Home](#)

username and password



# Document Database

[Instructions](#)

[Your Account](#)

[Preferences](#)

[DocDB Statistics](#)

[About DocDB](#)

[Create or change documents or other information](#)

Search

for

[\(Advanced\)](#)

Show

LARTPC-doc #

-v

Show

documents modified in the last

20

days

[Calendar of events](#)

List:

◊ [Authors](#)    ◊ [All documents](#)


◊ [Topics](#)

◊ [Groups](#)

◊ [Keywords](#)

◊ [Events](#)

### Schematic of Liquid Argon Purity Monitor (PrM)





2/5/06

1st Good Signal in Liquid, 2/3/06

1


Measure 't' , infer  $\tau$

PrM drawing




C.Kendziora2/3.05

PrM photograph



$$t_{\text{drift}} = 150 \mu\text{s}, Q_{\text{anode}}/Q_{\text{cathode}} = \sim 1$$



10/2007


sensitivity to temperature

## Issues:

do not know long term (years) photo-cathode sensitivity

requires non-solarizable quartz fibers,  $\lambda \sim 1$  meter

how many? (reliability, and spatial variations in liquid)



feedthrough (for Jack)